



ASME FLANGED & DISHED HEADS

Standard Sizes and Thickness' Available

Thickness Diameter	0.188	0.250	0.313	0.375	0.4375	0.500	0.625	0.750	0.875	1.000	1.125	1.250
8.625		X	X	X								
10.75	X	X	X	X								
12.75	X	X	X	X								
14.00		X	X	X								
16.00	X	X	X	X								
18.00	X	X	X	X	X							
20.00	X	X	X	X								
22.00			X									
24.00	X	X	X	X								
26.00												
28.00	X	X	X	X	X	X						
30.00	X	X	X	X	X	X	X					
32.00	X	X	X	X	X	X	X					
34.00	X	X	X	X	X	X	X					
36.00	X	X	X	X	X	X	X					
42.00	X	X	X	X	X	X	X					
48.00	X	X	X	X	X	X	X					
54.00	X	X	X	X	X	X	X					
60.00	X	X	X	X	X	X	X					
66.00	X	X	X	X	X	X	X	A				
72.00	X	X	X	X	X	X	X	A				
78.00	X	X	X	X	X	X	X	A				
84.00	X	X	X	X	X	X	X	A	A	A	A	A

X - Cold formed by C.E. Macpherson

A - Available from C.E. Macpherson, manufactured by affiliates.